

H01N2-D, H01N2-E

Welding cable up to 100 V

Konstrukce

- Fine stranded bare copper conductor according to DIN VDE 0282 cl. 6
- Separating polyester foil
- Neoprene core insulation
- Sheath color black
- According to DIN VDE 0482-332-1-2/ IEC 60332-1-2
- Oil resistant

Použití

These cables are used as a connection to welding generator and hand welding pliers or welding robots in automotive industry, shipyards etc. Robust cable structure of these cables makes them resistant to low and high temperatures, fire, ozone and radiation, oils, acids, fats and petrols. These cables are also ideal for outside installation in dry, moist and wet areas.

Technická data

- Special cable according to DIN VDE 0282 part 6 or HD 22.6 S2
- Temperature range from -25°C to +85°C
- Short-term permitted temperature at conductor max. 250°C
- Nominal voltage 100 V
- Test voltage a.c. 1000 V
- Minimum bending radius
 - H01N2-D: to 35 mm² 10x cable Ø
 - H01N2-D: 50 mm² and above 12x cable Ø
 - H01N2-E: to 35 mm² 7,5x cable Ø
 - H01N2-E: 50 mm² and above 10x cable Ø

Popis produktu

Note:

- CE = the product is conformed with the EC Low-Voltage Directive 2014/35/EU.
- Conforms to RoHS.

